

LUBRILAM S 55 L



Metalworking



UTILISATIONS

- Aluminium rolling non staining and viscous base stock.

ADVANTAGES

- Very low aromatic (0.03%) and sulfur content.
- High thermal and UV resistance.
- High flash point.
- Low volatility resulting in less losses by evaporation.
- Synergy with LUBRILAM ADD, rolling additives to reduce energy consumption and increase productivity.

TYPICAL CHARACTERISTICS	METHODS	UNITS	LUBRILAM S 55 L
Density at 15°C	EN ISO 12185	kg/m ³	815
Saybolt colour	ASTM D 156	-	+ 30 mini.
Distillation:	ISO 3405	-	
- initial point		°C	275 mini.
- dry point		°C	330 maxi.
Pensky-Martens flash point	EN ISO 2719	°C	≥ 130
Pour point	ISO 3016	°C	- 15
Aromatics content	TS IL 13 (U.V.)	% mass	0.03 maxi.
Viscosity at 20 °C	EN ISO 3104	mm ² /s	7.0
Viscosity at 40 °C	EN ISO 3104	mm ² /s	4.1
Benzene content	ASTM D 4367	ppm	1 maxi.
Aniline point	ISO 2977	°C	92
Sulfur content	ASTM D 3120	ppm	1 maxi.

Above characteristics are mean values given as an information.

**TOTAL LUBRIFIANTS
INDUSTRIE**

15-02-2018 (supersedes 01-04-2014)

LUBRILAM S 55 L

1/1



This lubricant used as recommended and for the application for which it has been designed does not present any particular risk.

A material safety data sheet conforming to the regulations in use in the E.C. can be obtained from your local commercial adviser or down loaded from

www.quick-fds.com.