



# LDS FLUID

## SYNTHETIC HYDRAULIC FLUID

### Applications

Orange synthetic fluid for hydraulic systems of Citroen vehicles equipped with HYDRACTIVE 3 Do not use when a fluorescent green mineral fluid is required (LHM Plus).

NB - An opened can of LDS fluid must be capped and kept in a clean place. A can of LDS fluid must be used within two weeks of opening, after this date discard the unused LDS fluid.

### Customer benefits

- Super multigrade fluid
- Exceptionally high viscosity index
- Very low pour point
- Very high thermal stability
- Exceptional protection against wear and corrosion
- Excellent lubricity
- Contributes to improved comfort

### Specifications

- PSA S71 2710

### Caractéristiques\*

| Essai                  | Unité              | Méthode d'essai | Résultat |
|------------------------|--------------------|-----------------|----------|
| Masse volumique à 15°C | kg/m <sup>3</sup>  | ASTM D 1298     | 820      |
| Viscosité à 40 °C      | mm <sup>2</sup> /s | ASTM D445       | 18       |
| Viscosité à 100 °C     | mm <sup>2</sup> /s | ASTM D445       | 5.9      |
| Indice de viscosité    | -                  | ASTM D2270      | 320      |
| Viscosité à -40°C      | mPa.s              |                 | 1 050    |
| Point d'écoulement     | °C                 | ASTM D97        | -51      |
| Point éclair           | °C                 |                 | 157      |

\* The above-mentioned characteristics are obtained within the usual production tolerances and cannot be considered as specifications.

## Advice for use

---

Before using the product, it is important to check the vehicle's maintenance manual: the oil is changed according to the manufacturer's recommendations.

The product must not be stored at a temperature higher than 60°C, while avoiding exposure to strong sunlight, intense cold or strong temperature variations.

It is preferable to store the packages in a weatherproof location. If not, the drums should be stored horizontally to avoid possible contamination by water and the removal of the product label.

## Health, safety, and environment

---

Based on available toxicological information, this product is not expected to cause adverse health effects when used in the intended application and in accordance with the recommendations provided in the Material Safety Data Sheet (MSDS). It is available upon request from your local dealer or at [www.quickfds.fr](http://www.quickfds.fr).

This product must not be used for applications other than those for which it is intended.

When disposing of the used product, be sure to protect the environment and comply with local regulations.