Dynatrans CVT 10W-30

Transmissions

KEY DATA

Specific fluid for CVT transmissions equipping Agricultural & Public Works machinery.

INTERNATIONAL STANDARDS

- API GL-4

MANUFACTURER APPROVALS

- ZF TE-ML 06F
- MASSEY-FERGUSON CMS M1145

MEETS THE REQUIREMENTS OF

- MASSEY FERGUSON CMS M1143/DYNA VT
- CASE CVX
- STEYR : CVT

SUITABLE FOR

- transmissions :
- CNH MAT 3540
- DEUTZ TTV
- JOHN DEERE AUTOPOWER

APPLICATIONS

Dynatrans CVT 10W-30 is dedicated to lubrication of "Continuously Variable Transmissions" (CVT) installed on agricultural tractors and some construction equipment.
This lubricant is also perfectly adapted to traditional transmissions, wet clutch transmissions including those equipped with wet brakes.

Dynatrans CVT 10W-30 is also designed to lubricate hydraulic systems, power-assisted steering and power-take-offs (PTO) with wet clutches.

PERFORMANCES & CUSTOMERS BENEFITS

- Dynatrans CVT 10W-30 is adapted to a wide range of agricultural and Public Works equipment and helps to reduce the stock and the number of lubricants.
- Its characteristics specifically adapted to CVT systems, guarantee smooth and progressive transmission operation.
- Dynatrans CVT 10W-30 has also a very strong resistance to the temperature together with a high anti-wear performance assuring transmission durability.

CHARACTERISTICS*

TEST	UNIT	TEST METHOD	RESULT
Kinematic viscosity at 40°C	mm²/s	ASTM D445	71.8
Kinematic viscosity at 100°C	mm²/s	ASTM D445	10.8
Viscosity index	-	ASTM D2270	139
Pour point	°C	ASTM D97	-45

* The characteristics given above are obtained with a standard tolerance threshold during production and may not be considered specifications.

RECOMMENDATIONS FOR USE

Before using the product, the vehicle's maintenance guide should be checked. Oil changes should be carried out in accordance with the manufacturer's recommendations.

The product should not be stored at temperatures over 60°C. It should be kept away from sunlight, intense cold and extreme temperature fluctuations. If possible, the packaging should not be exposed to the elements. Otherwise, the drums should be laid horizontally in order to avoid any contamination from water and to prevent the product's label from rubbing off.

HEALTH, SAFETY AND THE ENVIRONMENT

Based on the toxicological information available, this product should not cause any adverse health effects, provided it is used for its intended purpose and in accordance with the recommendations laid out in the Safety Data Sheet (SDS).

This can be obtained on request from your local reseller and is available for consultation at https://ms-sds.totalenergies.com.

This product should not be used for any purposes other than the ones for which it is intended.

TotalEnergies

Some variations can be expected under normal production conditions, but these should not affect the product's expected performance irrespective of the site. The information contained in this document is subject to change without notice. Our products can be viewed on our website at www.lubricants.totalenergies.com.