

Dynatrans WS 75W-90

Transmissions

KEY DATA



Synthetic oil for transmissions with wet brakes of Agricultural & Public Works machinery

INTERNATIONAL STANDARDS

- 🔥 API GL-4
- 🔥 ISO VG : HV 100

SUITABLE FOR

- 🔥 CASE MS 1206/MS 1207/MS 1209
- 🔥 CNH MAT 3505/MAT 3509/MAT 3525/MAT 3526
- 🔥 NEW HOLLAND NH 410C/NH 410B
- 🔥 MASSEY FERGUSON CMS M1135/M1141/M1143/M1145
- 🔥 CLAAS / RENAULT AGRICULTURE
- 🔥 JOHN DEERE J20D

APPLICATIONS

Dynatrans WS 75W-90 has been especially developed for manual or powershift transmissions with wet brakes. This lubricant is also perfectly adapted to gearboxes and power-take-offs (PTO) with wet clutches. Dynatrans WS 75W-90 is also designed for low hypoid axles (with or without wet brakes) and hydraulic systems.

PERFORMANCES & CUSTOMERS BENEFITS

- 🔥 Dynatrans WS 75W-90 is adapted to a wide range of agricultural and Public Works equipment and helps to reduce the stock and the number of lubricants.
- 🔥 This lubricant shows excellent low temperature performances (protects friction brakes against sticking) and high temperature performances (protects against judder or excessive slip even in continuous and severe conditions, no brake noise).
- 🔥 Dynatrans WS 75W-90 has very good extreme pressure and anti-wear properties giving optimum protection of gears and hydraulic components.

CHARACTERISTICS*

TEST	UNIT	TEST METHOD	RESULT
Kinematic viscosity at 40°C	mm ² /s	ASTM D445	106
Kinematic viscosity at 100°C	mm ² /s	ASTM D445	15.3
Viscosity index	-	ASTM D2270	150
Pour point	°C	ASTM D97	-48

*The characteristics given above are obtained with a standard tolerance threshold during production and may not be considered specifications.

RECOMMENDATIONS FOR USE

Before using the product, the vehicle's maintenance guide should be checked. Oil changes should be carried out in accordance with the manufacturer's recommendations.

The product should not be stored at temperatures over 60°C. It should be kept away from sunlight, intense cold and extreme temperature fluctuations. If possible, the packaging should not be exposed to the elements. Otherwise, the drums should be laid horizontally in order to avoid any contamination from water and to prevent the product's label from rubbing off.

HEALTH, SAFETY AND THE ENVIRONMENT

Based on the toxicological information available, this product should not cause any adverse health effects, provided it is used for its intended purpose and in accordance with the recommendations laid out in the Safety Data Sheet (SDS).

This can be obtained on request from your local reseller and is available for consultation at <https://ms-sds.totalenergies.com>.

This product should not be used for any purposes other than the ones for which it is intended.

