

# Neptuna SPEEDER 10W-40

Gasoline & Diesel engine oil

## KEY DATA



Synthetic oil for 4-stroke outboard gasoline & diesel engines running at high speed.

### INTERNATIONAL STANDARDS

- 🔥 ACEA A3/B4
- 🔥 API SN/CF

### SUITABLE FOR

- 🔥 HONDA
- 🔥 YAMAHA
- 🔥 BOMBARDIER
- 🔥 EVINRUDE
- 🔥 JOHNSON
- 🔥 MERCURY
- 🔥 SUZUKI
- 🔥 SEA-DOO

## APPLICATIONS

Neptuna SPEEDER 10W-40 is a synthetic lubricant developed for recent 4 strokes outboard gasoline and diesel engines running at high engine speed.

It is particularly recommended for marine outboard applications.

## PERFORMANCES & CUSTOMERS BENEFITS

- 🔥 Neptuna SPEEDER 10W-40 exhibits excellent shear resistance, ensuring very high oil film resistance under all conditions.
- 🔥 Outstanding detergent and dispersant properties keep the engine clean and guarantee sustained engine performance.
- 🔥 The association of anti-wear and antioxidant ensure extended engine lifespan.
- 🔥 Its anti-rust and anti-corrosion properties protect the engine from moisture damages.

## CHARACTERISTICS\*

| TEST                         | UNIT  | TEST METHOD | RESULT |
|------------------------------|-------|-------------|--------|
| Kinematic viscosity at 40°C  | mm²/s | ASTM D445   | 97     |
| Kinematic viscosity at 100°C | mm²/s | ASTM D445   | 14.5   |
| Flash Point                  | °C    | ASTM D92    | 230    |
| Viscosity index              | -     | ASTM D2270  | 155    |
| Pour point                   | °C    | ASTM D97    | -27    |

\*The characteristics given above are obtained with a standard tolerance threshold during production and may not be considered specifications.

## RECOMMENDATIONS FOR USE

Before using the product, the vehicle's maintenance guide should be checked. Oil changes should be carried out in accordance with the manufacturer's recommendations.

The product should not be stored at temperatures over 60°C. It should be kept away from sunlight, intense cold and extreme temperature fluctuations. If possible, the packaging should not be exposed to the elements. Otherwise, the drums should be laid horizontally in order to avoid any contamination from water and to prevent the product's label from rubbing off.

## HEALTH, SAFETY AND THE ENVIRONMENT

Based on the toxicological information available, this product should not cause any adverse health effects, provided it is used for its intended purpose and in accordance with the recommendations laid out in the Safety Data Sheet (SDS).

This can be obtained on request from your local reseller and is available for consultation at <https://ms-sds.totalenergies.com>.

This product should not be used for any purposes other than the ones for which it is intended.

