

Prosylva Chain Classic

Chainsaw oil

KEY DATA



ISO VG 100 Chain oil for Loss lubrication of Chainsaw and high speed machinery.

APPLICATIONS

Prosylva Chain Classic is dedicated to all **high speed machineries**: manual or mechanical chainsaw, Chain conveyors.

This lubricant is adapted to **all wood transformation**.

Prosylva Chain Classic is mainly adapted to the **lubrication of mechanical chainsaw** installed in wood cutting machines.

PERFORMANCES & CUSTOMERS BENEFITS

- 💧 Prosylva Chain Classic has very **adhesive behaviour** which reduces spattering and guarantees the lubrication on the entire length of the moving Chain.
- 💧 Prosylva Chain Classic exhibits lots of **properties**:
 - Reinforced anti-wear additivation
 - Improved anti-rust property
 - Friction reduction
 - Chain and guide wear reduction
 - Spattering, pollution and oil consumption reductions

CHARACTERISTICS*

TEST	UNIT	TEST METHOD	RESULT
Density at 15°C	kg/m ³	ASTM D1298	883
Kinematic viscosity at 40°C	mm ² /s	ASTM D445	100
Pour point	°C	ASTM D97	-33
Behavior	-	-	Adhesive

*The characteristics given above are obtained with a standard tolerance threshold during production and may not be considered specifications.

RECOMMENDATIONS FOR USE

Before using the product, the vehicle's maintenance guide should be checked. Oil changes should be carried out in accordance with the manufacturer's recommendations.

The product should not be stored at temperatures over 60°C. It should be kept away from sunlight, intense cold and extreme temperature fluctuations. If possible, the packaging should not be exposed to the elements. Otherwise, the drums should be laid horizontally in order to avoid any contamination from water and to prevent the product's label from rubbing off.

HEALTH, SAFETY AND THE ENVIRONMENT

Based on the toxicological information available, this product should not cause any adverse health effects, provided it is used for its intended purpose and in accordance with the recommendations laid out in the Safety Data Sheet (SDS).

This can be obtained on request from your local reseller and is available for consultation at <https://ms-sds.totalenergies.com>.

This product should not be used for any purposes other than the ones for which it is intended.

