



Description

ELF MOTO CHAIN PASTE is an extreme pressure grease intended to lubricate the motorcycle chain kit. Its excellent adhesion and strong water repellency make it the ideal lubricant to protect the chain in on-road riding conditions, especially in wet environments (urban environments by the sea, in winter, in rainy season...). The long-lasting effects of ELF MOTO CHAIN PASTE ensure increased safety and better comfort for the rider. The product is compatible with O, X and Z-rings.

Functions

- Protects the chain against corrosion and reduces friction so as to limit energy losses and risk of breakage
- Applicable on all motorcycle chains
- Adapted to extreme conditions (speed, load, temperature, humidity) on road

N. B. In off-road and adventure contexts, it is recommended to use ELF MOTO CHAIN LUBE as a substitute.

Instructions

- Prior information: optimal application on a hot chain (after a short run)
- Press the tube to pour product along the chain
- Use a brush to get the grease in
- Wait at least 10 minutes, ideally a few hours

N. B. ELF MOTO CHAIN PASTE must be applied on a clean surface, which can be cleaned with ELF MOTO DEGREASER+.

Benefits

- Outstanding extreme pressure properties
- Excellent corrosion resistance (calcium complex soap)
- Very strong water resistance
- Excellent mechanical stability
- High resistance to speed and temperature (-20°C to +150°C)
- Compatible with O, X and Z-rings

- White paste to ensure that the product has been applied throughout the chain

This lubricant, used according to our recommendations and for the application for which it is intended, does not present any particular risk. A safety data sheet in accordance with the legislation in force in the C.E. is available from your sales advisor.



MOTO CHAIN PASTE

Characteristics

ITEMS	METHOD	VALUE	UNI
Physical state	Visual	Liquid, smooth	-
Color	Visual	White	-
NLGI grade	[ASTM D 217]	1.5	-
Operating temperature range		from -20 to 150	°C
Penetration at 25 °C	[ASTM D 217]	29,5-33,5	mm
Four ball weld load	[ASTM D 2596]	>315	kgf
Water washout 1h at 80°C - weight loss	[ASTM D 1264]	<10	% wt
Dropping point	[IP 396]	>300	°C
Base oil	-	White oil	-
Kinematic viscosity of the base oil at 40 °C	[ISO 3104]	150	mm ² /s

* The characteristics given above are obtained with a standard tolerance threshold during production and may not be considered specifications.

Recommendations for Use

Before using the product, the vehicle's maintenance guide should be checked.

The product should not be stored at temperatures over 60°C. It should be kept away from sunlight, intense cold and extreme temperature fluctuations. If possible, the packaging should not be exposed to the elements.

Health, Safety and The Environment

Based on the toxicological information available, this product should not cause any adverse health effects, provided it is used for its intended purpose and in accordance with the recommendations laid out in the Safety Data Sheet (SDS).

The Safety Data Sheet can be obtained on request from your local reseller and is available for consultation at <https://elf.com/en>.

This product should not be used for any purposes other than the ones for which it is intended.

ELF Lubrifiants / www.elf.com

Updated on: #####

This lubricant, used according to our recommendations and for the application for which it is intended, does not present any particular risk. A safety data sheet in accordance with the legislation in force in the C.E. is available from your sales advisor.