



Technical datasheet

Description

ELF MOTO DEGREASER+ is an aerosol for cleaning the motorcycle. It removes persistent dirt, including traces of grease and dust. It is compatible with all metal parts and is particularly recommended for the degreasing of clutch and brake systems as well as for the cleaning of the chain kit.

Functions

- Degreasing of the clutch system
- Degreasing of the brake system
- Cleaning of the chain kit before lubrication*
- Also removes lubricants for chain that have agglomerated too many abrasive materials
- Also applicable on other metal parts: candles, carburetor, etc.

* recommended with ELF MOTO CHAIN LUBE or ELF MOTO CHAIN PASTE

Instructions

- Spray surfaces to be treated without excess
- Use a brush if dirt is thick
- Wipe with a clean cloth (after leaving for up to 8 minutes in case of stubborn marks)

N. B. The product is not aggressive on plastic parts and is also compatible with O, X and Z-ring chains.

Benefits

- Strong degreasing power (kauri-butanol value: 90; vs. 30 for commonly available products)
- 3-in-1 product: degreaser, brake cleaner, and chain cleaner
- 97% active substance, natural compressed gas
- High pressure (5 bar) for enhanced mechanical action

Performance

- Quick drying
- Can be used in all positions
- Directional spray for targeted application
- Leaves no residue

Convenience

Characteristics

ITEMS	METHOD	VALUE	UNITS
Physical state	Visual	Liquid	-
Color	Visual	Colorless	-
Smell	Olfactory	Light	-
Refractive index	[ISO 5661]	1,411	-
Flash point	Close cup [ISO 2719]	23	°C
Flammability	-	Flammable	-
Lower and upper explosion limit	-	Upper: 5,8% Lower: 0,4%	-
Vapor pressure at 20°C	-	>0,1	hPa
Freezing point	[ISO 3016]	-30	°C
Residue after evaporation	[NF T 30-084]	0	%
Evaporation speed	-	9	minutes
Solubility in water	-	Partial	-
Surface tension at 20°C	[ISO 6295]	<21,4	Dynes/cm
KB index (kauri-butanol)	[ASTM D 1133]	90	-
Biodegradability	OCDE approved	Easily biodegradable	-
Auto-ignition temperature	[ASTM E 659]	240	°C
Kinematic viscosity at 40°C	[NF EN 3104]	1,8	mm ² /s

* The characteristics given above are obtained with a standard tolerance threshold during production and may not be considered specifications.

Technical datasheet

Recommendations for Use

Before using the product, the vehicle's maintenance guide should be checked.

The product should not be stored at temperatures over 50°C. It should be kept away from sunlight, intense cold and extreme temperature fluctuations. If possible, the packaging should not be exposed to the elements.

Health, Safety and The Environment

Based on the toxicological information available, this product should not cause any adverse health effects, provided it is used for its intended purpose and in accordance with the recommendations laid out in the Safety Data Sheet (SDS).

The Safety Data Sheet can be obtained on request from your local reseller and is available for consultation at <https://elf.com/en>.

This product should not be used for any purposes other than the ones for which it is intended.