



ELF MOTO FORK OIL 10W, 15W, 20W

New generation semi-synthetic lubricant.

USE

- **Motorcycle application**
 - Specially formulated to meet the requirements of all different types of motorcycle telescopic forks and hydraulic shock absorbers.
 - The different grades are perfectly suitable for all types of machine (road or off-road), all types of riding conditions (solo or two-up) and different riding situations (leisure or competition).

PERFORMANCES

- **Mineral oils**
 - Selected "hydraulic quality" mineral oil based formulae.
- **SAE 10 – 15 et 20W**
 - Wide viscosity range suitable for all applications.

CUSTOMER ADVANTAGES

- **Anti-wear**
 - MOTO FORK OILS are composed of selected mineral compounds reinforced by special additives conferring upon them numerous qualities such as a high anti-wear capacity.
- **Optimum damping**
 - This oil provides optimum damping all year round and is stable in time.
- **Rapid de-aeration**
 - Excellent behaviour in air: limited bubbling and very rapid de-aeration.
- **Elastomer compatibility**
 - Excellent compatibility with elastomers used in motorcycle forks and shock absorbers.

PROPERTIES

PHYSICAL-CHEMICAL PROPERTIES MOTO FORK OIL, 10W, 15W, 20W

Density at 15 °C	0.875	0.881	0.887	
Viscosity index	153	155	150	
Kinematic viscosity at 40 °C	47	72.6	99	mm ² /s
Kinematic viscosity at 100 °C	8.3	11.6	14.6	mm ² /s
Pour point	<-36	<-30	<-27	°C

The specifications in this table are averages given for information only.

TOTAL LUBRIFIANTS
Immeuble Spazio
562, avenue du Parc de l'île
92029 Nanterre cedex
France
1/1

ELF MOTO FORK OIL
05/2014



This multigrade lubricant when used according to our recommendations and for the purpose for which it is intended presents no particular hazard. A safety data sheet complying with current EC legislation can be obtained on www.quick-fds.com and from your local commercial advisor.