

This lubricant, used according to our recommendations and for the application for which it is intended, does not present any particular risk. A safety data sheet in accordance with the legislation in force in the C.E. is available from your sales advisor.

Characteristics

ITEMS	METHOD	VALUE	UNITS
Physical state	Visual	Liquid	-
Color	Visual	Amber	-
Smell	Olfactory	Pine scented	-
Refractive index	[ISO 5661]	1,455	-
Flash point	Close cup	64	°C
Copper blade corrosion 100h at 40°C	[ISO 2719]		
Lower and upper explosion limit	-	Upper: 7% Lower: 1%	-
Freezing point	[ISO 3016]	-20	°C
SRV Friction test	[ASTM D 5707]	0,09	Coefficient
Shell 4-ball test <i>Impression diameter</i>	[IP 239, ASTM D 2596]	0,52	mm
Shell 4-ball test <i>Weld load</i>	[IP 239, ASTM D 2596]	3200	daN
Surface tension at 20°C	[ISO 6295]	24,2	Dynes/cm
Indice kauri-butanol (KB index)	[ASTM D 1133]	97	-
Auto-ignition temperature	[ASTM E 659]	230	°C
Kinematic viscosity at 40°C	[NF EN 3104]	2,1	mm ² /s

* The characteristics given above are obtained with a standard tolerance threshold during production and may not be considered specifications.

Technical datasheet

Recommendations for Use

Before using the product, the vehicle's maintenance guide should be checked.

The product should not be stored at temperatures over 50°C. It should be kept away from sunlight, intense cold and extreme temperature fluctuations. If possible, the packaging should not be exposed to the elements.

Health, Safety and The Environment

Based on the toxicological information available, this product should not cause any adverse health effects, provided it is used for its intended purpose and in accordance with the recommendations laid out in the Safety Data Sheet (SDS).

The Safety Data Sheet can be obtained on request from your local reseller and is available for consultation at <https://elf.com/en>.

This product should not be used for any purposes other than the ones for which it is intended.