

TRANSELF NFP 75W-80 is adapted for Renault vehicles equipped with P, J, NDX, TL4 family gearboxes.

Technical Data Sheet

International Specifications

API GL-4

Manufacturers Approvals

Approved :
P TRANSMISSION
RENAULT JXX TRANSMISSION, RENAULT NDX TRANSMISSION,
RENAULT PXX TRANSMISSION, RENAULT TL4 TRANSMISSION

Meets the requirement of :
RENAULT TLX TRANSMISSION

* Refer to the maintenance book of your vehicle to know the recommendation of the manufacturer.

1 - Applications

TRANSELF NFP 75W-80 is especially recommended for easy gear changing in cold weather: also retains its outstanding qualities when hot, ensuring the smoothest possible operation and longer life for gearbox components.

2 - Customer Benefits

High-performance transmission fluid that improves speed changing at low temperatures, reduces noise during speed changes, prevents difficult disengagements and cracks.

Provides good protection for gear teeth under severe stress, maintains smooth speed changes throughout the gearbox's lifespan.

Enhances protection against wear on mechanical components.

3 - Characteristics

| TEST | TEST METHOD | UNITS | VALUE |
|------------------------------|-------------|--------------------|-------|
| Density at 15°C | ASTM D1298 | kg/m ³ | 868 |
| Kinematic Viscosity at 40°C | ASTM D445 | mm ² /s | 36 |
| Kinematic Viscosity at 100°C | ASTM D445 | mm ² /s | 7.5 |
| Viscosity index | ASTM D2270 | - | 182 |
| Pour point | ASTM D97 | °C | -51 |
| Flash point | ASTM D92 | °C | - |
| TBN | ASTM D2896 | mgKOH/g | - |
| Sulphated Ash | ASTM D874 | % m/m | - |

* The characteristics given above are obtained with a standard tolerance threshold during production and may not be considered specifications.

4 - Recommendations for Use

Before using the product, the vehicle's maintenance guide should be checked. Oil changes should be carried out in accordance with the manufacturer's recommendations.

The product should not be stored at temperatures over 60°C. It should be kept away from sunlight, intense cold and extreme temperature fluctuations. If possible, the packaging should not be exposed to the elements.

Otherwise, the drums should be laid horizontally in order to avoid any contamination from water and to prevent the product's label from rubbing off.

5 - Health, Safety and The Environment

Based on the toxicological information available, this product should not cause any adverse health effects, provided it is used for its intended purpose and in accordance with the recommendations laid out in the Safety Data Sheet (SDS).

The SDS is available on request from your local reseller and at <https://ms-sds.totalenergies.com>.

This product should not be used for any purposes other than the ones for which it is intended.