

TRANSELF NFX SAE 75W is adapted for all Renault-Nissan-Mitsubishi vehicles equipped with Manual Transmissions including Sx, Jxx, TLx, NDx, NDK1, Pxx, DBx family gearboxes.

Technical Data Sheet

International Specifications

API GL-4

Manufacturers Approvals

Approved :
MB-APPROVAL 235.17
RENAULT PXX TRANSMISSION, RENAULT SX TRANSMISSION, RENAULT JXX TRANSMISSION, RENAULT TLX TRANSMISSION, RENAULT NDx TRANSMISSION, RENAULT NDK1 TRANSMISSION, RENAULT DBx TRANSMISSION

* Refer to the maintenance book of your vehicle to know the recommendation of the manufacturer.

1 - Applications

TRANSELF NFX SAE 75W is especially recommended for easy gear changing in cold weather. This Lubricant also maintains its outstanding performances at high temperature, ensuring the smoothest possible operation and extended life of the gearbox components.

TRANSELF NFX SAE 75W replaces TRANSELF NFP 75W-80 and TRANSELF NFJ 75W-80 and covers their targeted applications.

2 - Customer Benefits

Provides advanced protection and exceptional performance for synchro components, with outstanding resistance to shear.

Demonstrates extreme-pressure capabilities, and stable thermal performance.

Offers stable synchronization and reliable lubrication at all temperatures.

3 - Characteristics

TEST	TEST METHOD	UNITS	VALUE
Density at 15°C	ASTM D1298	kg/m ³	847
Kinematic Viscosity at 40°C	ASTM D445	mm ² /s	31
Kinematic Viscosity at 100°C	ASTM D445	mm ² /s	6.5
Viscosity index	ASTM D2270	-	168
Pour point	ASTM D97	°C	-45
Flash point	ASTM D92	°C	-
TBN	ASTM D2896	mgKOH/g	-
Sulphated Ash	ASTM D874	% m/m	-

* The characteristics given above are obtained with a standard tolerance threshold during production and may not be considered specifications.

4 - Recommendations for Use

Before using the product, the vehicle's maintenance guide should be checked. Oil changes should be carried out in accordance with the manufacturer's recommendations.

The product should not be stored at temperatures over 60°C. It should be kept away from sunlight, intense cold and extreme temperature fluctuations. If possible, the packaging should not be exposed to the elements.

Otherwise, the drums should be laid horizontally in order to avoid any contamination from water and to prevent the product's label from rubbing off.

5 - Health, Safety and The Environment

Based on the toxicological information available, this product should not cause any adverse health effects, provided it is used for its intended purpose and in accordance with the recommendations laid out in the Safety Data Sheet (SDS).

The SDS is available on request from your local reseller and at <https://ms-sds.totalenergies.com>.

This product should not be used for any purposes other than the ones for which it is intended.