

NEVASTANE LUBE AEROSOL



Food Industry



**Multipurpose adhesive Oil for incidental food contact.
in aerosol 520 ml (300 ml net).**

APPLICATIONS

- **NEVASTANE LUBE AEROSOL** contains a thickened oil which is adhesive, translucent and at a high level of purity.
- **NEVASTANE LUBE AEROSOL** is recommended for the lubrication of numerous applications operating under severe conditions in food processing industries.
- **NEVASTANE LUBE AEROSOL** is multipurpose with a wide operating temperature range (-20°C to +150°C) : general maintenance lubrication, conveyors and rails, plain and roller bearings...

SPECIFICATIONS

- The formulation of **NEVASTANE LUBE AEROSOL** complies with the FDA chapter 21 CFR, 178.3570.
- **NEVASTANE LUBE AEROSOL** is NSF H1 registered: No 141647.
- **NEVASTANE LUBE AEROSOL** is recommended for use where incidental food contact is possible. That prevents contamination issues as required in the HACCP systems.

ADVANTAGES

- Excellent adhesion on metal surfaces.
- Lubricant without dropping point.
- Odour-free and flavorless lubricant.
- Very good resistance to water and steam.
- Good resistance to acids and weak bases.
- Compatible with the elastomers and plastics normally used in food machinery.
- Powerful and precise pulverization thanks to the mini-jet diffuser of the aerosol.

TYPICAL CHARACTERISTICS	METHODS	UNITS	NEVASTANE LUBE AEROSOL
Aspect	Visual	-	Smooth, tacky and homogeneous gel
Color	Visual	-	Colorless
Resistance to washing out by water at 80°C	ASTM D 2164	% mass	8
Base oil viscosity at 40°C	NF EN ISO 3104	mm ² /s	90

Above characteristics are mean values given as an information.

Recommendations:

- Shake well before use
- Hold upright and spray from a distance of about 20 cm
- Shelf life: 3 years from date of manufacture (unopened).

Cautions:

- Store between 0°C and 50°C
- Do not spray on a naked flame or any incandescent material

TOTAL LUBRIFIANTS
Industrie & Spécialités
17-05-2010 (supersedes 04-06-2009)
NEVASTANE LUBE AEROSOL
1/1



This lubricant used as recommended and for the application for which it has been designed does not present any particular risk.
A material safety data sheet conforming to the regulations in use in the E.C. can be obtained from your local commercial adviser or down loaded from www.quick-fds.com.