



Nevastane PTFE Grease Spray

DESCRIPTION

Multipurpose, NSF-H1-certified, high-PTFE-content white grease.

Keep away from daylight, dust, and humidity.

Shelf life: 2 years from date of manufacture.

CAUTION

Due to the container and the presence of solvents:

Keep away from heat, sparks, and flames.

Do not expose to heat and temperatures > 50°C.

Even when empty, do not puncture or incinerate the container.

APPLICATIONS

- Mineral codex silica gel grease – white grease for the use in wet atmosphere
- To be used in all kinds of Food & Beverages industries: Industrial bakeries, dairy industries, biscuit industry, canneries, slaughterhouses...
- More generally, to be used whenever a clean lubrication is needed (automotive, plumbing...)

ADVANTAGES

- Clean grease
- No dropping point
- Easy removal with organic solvents
- Non-flammable propellant gas: CO₂.

TYPICAL CHARACTERISTICS

PROPERTIES	Nevastane PTFE Grease Spray	UNITS	STANDARDS
Color	White	-	Visual
Aspect	Butyrous	-	Visual
Non-worked penetrability at 25°C	265 - 295	0.1mm	DIN ISO 2137
Dropping point	N/A (infusible)	°C	ASTM D 566
Four Ball welding load	200	kg	ASTM D 2596
Operating temperature range	-10 to 180 (peak : 200°C)	°C	-

This lubricant used as recommended and for the application for which it has been designed does not present any particular risk.

A material safety data sheet conforming to the regulations in use in the E.C. can be obtained from your local commercial adviser or downloaded at www.quick-fds.com.