

Caprano SPECIAL PLUS 40

Lubricant for 4 stroke high speed and medium speed Diesel

KEY DATA



Monograde Lubricant for **fast & medium speed 4-stroke Diesel engines used in navigation.**

INTERNATIONAL STANDARDS

- ACEA E7
- API CH-4/CG-4/CF-4/CF

MANUFACTURER APPROVALS

- ABC: 6DZ and 8DZ in line (SAE 30)
- ABC: 12DZ and 16DZ in V (SAE 40)

APPLICATIONS

Caprano SPECIAL PLUS 40 is recommended for **fast speed and medium speed Diesel engines** (turbocharged or naturally-aspirated) used in inland and coastal shipping.

This lubricant is also adapted to **transmissions systems.**

PERFORMANCES & CUSTOMERS BENEFITS

- Caprano SPECIAL PLUS 40 offers **excellent thermal stability** and **oxidation resistance**, guaranteeing effective engine lubrication in severe conditions.
- Outstanding detergent, dispersant and anti-wear properties** keep the engine clean and enable effective control of soot, sludge and piston deposits.
- These lubricants are adapted to fuel with up to 0.5% sulphur content.
- Its **anti-wear** and **anti-corrosion** additives ensure longer engine and transmission durability.

CHARACTERISTICS *

TEST	UNIT	TEST METHOD	RESULT
Density at 15°C	kg/m ³	ASTM D1298	896
Kinematic viscosity at 40°C	mm ² /s	ASTM D445	139
Kinematic viscosity at 100°C	mm ² /s	ASTM D445	14.9
Viscosity index	-	ASTM D2270	108
Pour point	°C	ASTM D97	-30
T.B.N	mgKOH/g	ASTM D2896	13

*The characteristics given above are obtained with a standard tolerance threshold during production and may not be considered specifications.

RECOMMENDATIONS FOR USE

Before using the product, the vehicle's maintenance guide should be checked. Oil changes should be carried out in accordance with the manufacturer's recommendations.

The product should not be stored at temperatures over 60°C. It should be kept away from sunlight, intense cold and extreme temperature fluctuations. If possible, the packaging should not be exposed to the elements. Otherwise, the drums should be laid horizontally in order to avoid any contamination from water and to prevent the product's label from rubbing off.

HEALTH, SAFETY AND THE ENVIRONMENT

Based on the toxicological information available, this product should not cause any adverse health effects, provided it is used for its intended purpose and in accordance with the recommendations laid out in the Safety Data Sheet (SDS).

This can be obtained on request from your local reseller and is available for consultation at <https://ms-sds.totalenergies.com>.

This product should not be used for any purposes other than the ones for which it is intended.

