

Neptuna GEAR 80W-90

Transmission oil

KEY DATA



Very high performance lubricant for transmissions & gears used in leisure boating.

INTERNATIONAL STANDARDS

🔥 API GL-4 / GL-5

MEETS THE REQUIREMENTS OF

🔥 MERCURY

APPLICATIONS

Neptuna GEAR 80W-90 is specially recommended for loaded gears used in outdrives and transmissions of leisure craft.

Also suitable for all transmission systems using gears, bevel gears, step-down gears, etc...

PERFORMANCES & CUSTOMERS BENEFITS

- 🔥 Neptuna GEAR 80W-90 is particularly efficient at high temperature and under heavy loads.
- 🔥 This product assures extreme pressure protection and withstands attacks due to marine environment humidity and acidity.
- 🔥 Its exclusive compound formula confers upon its operability at all temperatures: from the lowest (-30°C) to the highest (130°C).
- 🔥 Neptuna GEAR 80W-90 insures advance anti-wear and anti-corrosion protection.
- 🔥 No foaming or emulsification when in service.

CHARACTERISTICS *

TEST	UNIT	TEST METHOD	RESULT
Density at 15°C	kg/m ³	ASTM D1298	897
Kinematic viscosity at 40°C	mm ² /s	ASTM D445	140
Kinematic viscosity at 100°C	mm ² /s	ASTM D445	15
Viscosity index	-	ASTM D2270	105
Pour point	°C	ASTM D97	-27

*The characteristics given above are obtained with a standard tolerance threshold during production and may not be considered specifications.

RECOMMENDATIONS FOR USE

Before using the product, the vehicle's maintenance guide should be checked. Oil changes should be carried out in accordance with the manufacturer's recommendations.

The product should not be stored at temperatures over 60°C. It should be kept away from sunlight, intense cold and extreme temperature fluctuations. If possible, the packaging should not be exposed to the elements. Otherwise, the drums should be laid horizontally in order to avoid any contamination from water and to prevent the product's label from rubbing off.

HEALTH, SAFETY AND THE ENVIRONMENT

Based on the toxicological information available, this product should not cause any adverse health effects, provided it is used for its intended purpose and in accordance with the recommendations laid out in the Safety Data Sheet (SDS).

This can be obtained on request from your local reseller and is available for consultation at <https://ms-sds.totalenergies.com>.

This product should not be used for any purposes other than the ones for which it is intended.

