

Prosylva 2T SYN

Engine oil

KEY DATA



Synthetic oil designed for 2-stroke engines used in mechanized farming.

INTERNATIONAL STANDARDS

- 🔥 API TC
- 🔥 JASO FD
- 🔥 ISO L-EGC/EGD (detergent level)

MEETS THE REQUIREMENTS OF

- 🔥 HUSQVARNA
- 🔥 ROTAX
- 🔥 STIHL

APPLICATIONS

Prosylva 2T SYN is particularly adapted to **2 stroke engines**, for **gardening** and **mechanized farming** working under continuous **heavy loads** and at **high temperature**.

Its viscosity is tailored to be used in a **mixture with gasoline** or **in separate greasing**. Prosylva 2T SYN is also adapted to **unleaded gasoline**.

PERFORMANCES & CUSTOMERS BENEFITS

- 🔥 Prosylva 2T SYN offers **outstanding thermal stability**, ensuring efficient lubrication of hot engine parts.
- 🔥 Its **exceptional oil film resistance when hot** guarantees good engines operation and no performance losses.
- 🔥 This lubricant is **miscible** with gasoline and produces a **homogeneous** and **stable mixture**. Its blue color allows to distinguish mixture already containing oil, and to avoid using pure gasoline in the engine.
- 🔥 Prosylva 2T SYN has good ability to **complete combustion**, ensuring exhaust deposits and smoke reduction.
- 🔥 Its low ash content (0.07%) avoids spark plug fouling and piston deposits.
- 🔥 Its **anti-rust** and **anti-corrosion properties** protect the engine from moisture damages.

CHARACTERISTICS*

TEST	UNIT	TEST METHOD	RESULT
Density at 15°C	kg/m ³	ASTM D1298	869
Kinematic viscosity at 40°C	mm ² /s	ASTM D445	76.1
Kinematic viscosity at 100°C	mm ² /s	ASTM D445	10.9
Viscosity index	-	ASTM D2270	132
Pour point	°C	ASTM D97	-21
Sulphated Ash	°C	ASTM D874	0.07
Color	-	-	Blue

*The characteristics given above are obtained with a standard tolerance threshold during production and may not be considered specifications.

RECOMMENDATIONS FOR USE

Before using the product, the vehicle's maintenance guide should be checked. Oil changes should be carried out in accordance with the manufacturer's recommendations.

The product should not be stored at temperatures over 60°C. It should be kept away from sunlight, intense cold and extreme temperature fluctuations. If possible, the packaging should not be exposed to the elements. Otherwise, the drums should be laid horizontally in order to avoid any contamination from water and to prevent the product's label from rubbing off.

HEALTH, SAFETY AND THE ENVIRONMENT

Based on the toxicological information available, this product should not cause any adverse health effects, provided it is used for its intended purpose and in accordance with the recommendations laid out in the Safety Data Sheet (SDS).

This can be obtained on request from your local reseller and is available for consultation at <https://ms-sds.totalenergies.com>.

This product should not be used for any purposes other than the ones for which it is intended.

